










Lamp Mounting Height Cross-reference Table

Lamp type	T&B Lamp No.	Wattage	Maximum Mounting Height (feet) for open lamp units 	Maximum Mounting Height (feet) for enclosed lamp units 
MR16 Halogen 	580.0072	6V-5W Flood	8	8
	580.0074	6V-6W Flood	10	10
	580.0079	6V-10W Flood	25	20
	580.0099	12V-10W (38D)	12	12
	580.0080	12V-12W Flood	15	15
	580.0064	12V-20W Flood	20	20
	580.0068	12V-20W HO Flood	30	25
	580.0075	12V-20W AI Flood	20	20
	580.0083	12V-35W Di Flood	50	45
	580.0090	12V-35W HO Flood	55	50
	580.0076	12V-50W Di Flood	50	45
	580.0089	12V-50W HO Flood	70	65
Lamp type	T&B Lamp No.	Wattage	Maximum Mounting Height (feet) for open lamp units	Maximum Mounting Height (feet) for enclosed lamp units
MR 16 LED 	580.0093	12V-4W	25	25
	580.0104	12V-5W	25	25
	580.0106	12V-6W	40	35
Lamp type	T&B Lamp No.	Wattage	Maximum Mounting Height (feet) for PAR18 heads 	Maximum Mounting Height (feet) for PAR36 heads 
Wedge base T5, T8 	570.0012	6v-5.4w	7	7
	570.0026	6v-7.2w	7	7
	570.0016	6v-9w	16	10
	570.0025	12v-9w	15	15
	570.0045	24v-9w	16	10
	570.0028	12v-12w	10	10
	570.0029	12v-18w	15	15
	570.0046	24v-18w	15	15

Lamp type	T&B Lamp No.	Wattage	Maximum Mounting Height (feet) for PAR18 heads	Maximum Mounting Height (feet) for PAR36 heads
Bi-Pin Halogen T2-3/4, T2-1/4 	580.0012	6v-6w	15	12
	580.0018	6v-8w	15	12
	580.0014	12v-8w	18	15
	580.0017	6v-10w	18	15
	580.0011	6v-12w	12	18
	580.0015	12v-12w	20	15
	580.0022	6v-20w	N/A	20
	580.0027	12v-20w	N/A	20
Lamp type	T&B Lamp No.	Wattage	Maximum Mounting Height (feet) for PAR18 heads	Maximum Mounting Height (feet) for PAR36 heads
DC-Bayonet 	570.0010	6v-9w	N/A	12
	570.0011	12v-9w	N/A	12
	570.0020	6v-12w	N/A	10
	570.0037	6v-18w	N/A	15
	570.0030	12v-18w	N/A	20
	570.0038	6v-25w	N/A	20
	570.0031	12v25w	N/A	25
Lamp type	T&B Lamp No.	Wattage	Maximum Mounting Height (feet) for PAR18 heads	Maximum Mounting Height (feet) for PAR36 heads
H1 / H3	580.0030	12v-55w	N/A	42
	580.0081	24v-70w	N/A	43
Lamp type	T&B Lamp No.	Wattage	Maximum Mounting Height (feet) for PAR18 heads	Maximum Mounting Height (feet) for PAR36 heads
Sealed Beam Incandescent PAR 36 	550.0018	6v-8w	N/A	20
	550.0026	12v-12w	N/A	18
	550.0027	12v-18w	N/A	20
	550.0017	6v-25w	N/A	25
	550.0023	12v-25w	N/A	18
	550.0035	6v-30w	N/A	25
	550.0034	12v-30w	N/A	25
Lamp type	T&B Lamp No.	Wattage	Maximum Mounting Height (feet) for PAR18 heads	Maximum Mounting Height (feet) for PAR36 heads
Seald Beam Halogen PAR 36 	550.0022	6v-6w	N/A	17
	550.0024	12v-8w	N/A	20
	550.0037	6v-10w	N/A	25
	550.0019	6v-12w	N/A	20
	550.0025	12v-12w	N/A	25
	550.0021	6v-20w	N/A	35
	550.0047	12v-37w	N/A	60
	550.0012	12v-50w	N/A	35
Lamp type	T&B Lamp No.	Wattage	Fixture type	Maximum Mounting Height (feet)
LED Lamp		Std-Fwd Throw	LED Emergency Lighting Unit 	15
		Std-Wide		15
		HT-Fwd Trow		20
		HT-Wide		15

Lamp type	T&B Lamp No.	Wattage	Fixture type	Maximum Mounting Height (feet)
MR16 	580.0093	4W LED	Enclosed ribbed lens 	8
	580.0080	12v - 12w		8
	580.0064	12v - 20w		8
	580.0068	12v - 20w HO		8

1. Above maximum mounting heights are based on the performance of lamping only and are not to be used for photometric purposes, and are based on 0 ft spacing.
2. Emergency lighting layouts must be based on the photometric information provided with each product.
3. Regardless of the context of the installation, the final mounting height must be lower than stipulated above.