

Surface Mounted Series

Remote Emergency Lighting Fixtures



EF18/EF18D/EF18T Series

- PAR36, surface-mounted, large remote fixtures
- Single, double or triple head
- Positive aim swivel
- Available in factory white (standard) and black



EF26/EF26DS/EF26D Series

- Cubic, vandal-resistant surface-mounted fixture
- Single, double or twin cube with center body
- Available in factory white (standard) and black with frosted polycarbonate cube



Project/Location:

Date:

C

A

PM

I

LS

Contractor:


Prepared by:

Surface Mounted Series

EF18/EF18D/EF18T

Dimensions

EF18:	4.5" (11.4 cm) L x 7.25" (18.4 cm) H x 3.5" (8.9 cm) D Canopy: 5.0" (12.7 cm) Diameter
EF18D:	4.5" (11.4 cm) L x 7.25" (18.4 cm) H x 11.75" (29.9 cm) D Canopy: 5" (12.7 cm) Diameter
EF18T:	14.0" (35.6 cm) L x 7.25" (18.4 cm) H x 14.0" (35.6 cm) D Canopy: 9.5" (24.1 cm) Diameter



Ordering Information

Series	Lamp Style	Colour	Lamp Type/Voltage/Wattage	Options
EF18= single, par 36	Blank= tungsten	Blank= factory white	-6V9W= 6V - 9 watts, tungsten, wedge base	FP= teflon coated lens
EF18D= double, par 36	Q= halogen	B= black	-6V __ W= 6V - 18 or 25 watts, tungsten, D.C.B	
EF18T= triple, par 36	S= sealed beam		-12V __ W= 12V - 9 or 18 watts, tungsten, wedge base	
	H= quartz sealed beam		-12V25W= 12V - 25 watts, tungsten, D.C.B.	
			-24V __ W= 24V - 9 or 18 watts, tungsten, wedge base	
			-24V25W= 24V - 25 watts, tungsten, D.C.B.	
			-6V __ W= 6V - 8, 12, or 20 watts, halogen, quartz bi-pin	
			-12V __ W= 12V - 8, 12, 20 or 55 watts, halogen, quartz bi-pin	
			-24V __ W= 24V - 20 or 70 watts, halogen, quartz bi-pin	
			-6V __ W= 6V - 8, 12, 18 or 25 watts, tungsten, sealed beam	
			-12V __ W= 12V - 12, 18 or 25 watts, tungsten, sealed beam	
			-6V __ W= 6V - 8, 12 or 20 watts, halogen, quartz sealed beam	
			-12V __ W= 12V - 8, 12 or 37 watts halogen, quartz sealed beam	
			-32V __ W= 32V - 18 or 25 watts, tungsten, D.C.B.	
			-120V __ W= 120V - 10 or 15 watts, tungsten, D.C.B.	
			-120V 35W= 120V 35 watts, halogen, D.C.B.	
			-120V 50W= 120V 50 watts, halogen, D.C.B.**	
			*NOTE: " __ " = insert wattage required	
			**Available with metal heads only.	

EXAMPLE: EF18Q-12V12W

EF26

Dimensions

EF26:	4.4" (11.2 cm) L x 4.8" (12.2 cm) H x 4.4" (11.2 cm) D
EF26D:	9.4" (23.9 cm) L x 5.75" (14.6 cm) H x 4.4" (11.2 cm) D
EF26DS:	14.8" (37.6 cm) L x 4.88" (12.4 cm) H x 4.88" (12.4 cm) D



Ordering Information

Series	Lamp Style	Colour	Options	Lamp Style/Wattage
EF26= single cube	Blank= tungsten	Blank= factory white	Blank= no options	-6V9W= 6V - 9 watts, tungsten wedge base
EF26D= double cube	Q= halogen	B= black	TP= tamper proof screws	-12V9W= 12V - 9 watts, tungsten wedge base
EF26DS= twin cube	M= halogen, MR 16			-12V18W= 12V - 18 watts, tungsten wedge base
				-24V9W= 24V - 9 watts, wedge base
				-6V8W= 6V - 8 watts, quartz bi-pin
				-6V12W= 6V - 12 watts, quartz bi-pin
				-12V8W= 12V - 8 watts, quartz bi-pin
				-12V12W= 12V - 12 watts, quartz bi-pin
				-24V20W= 24V - 20 watts, quartz bi-pin
				-6V6W= 6V - 6 watts, MR16
				-6V10W= 6V - 10 watts, MR16
				-12V12W= 12V - 12 watts, MR16
				-12V20W= 12V - 20 watts, MR16
				-12V35W= 12V - 35 watts, MR16
				-12V50W= 12V - 50 watts, MR16
				-24V20W= 24V - 20 watts, MR16
				-24V35W= 24V - 35 watts, MR16
				-24V50W= 24V - 50 watts, MR16
				-120V35W= 120V - 35 watts, halogen, D.C.B.

EXAMPLE: EF26Q-TP-6V8W

Thomas & Betts

© Thomas & Betts Limited. All rights reserved.

www.emergi-lite.com

EMERGI-LITE

Printed in Canada. 03/07/500. Order no. EL/SMS-E