



PRO-2 Series

The PRO-2 can be mounted in any orientation on walls or ceilings.

Listed to UL 924 Standard, Sealed Maintenance-Free Battery, Lead Calcium

General Information

The Provider Series is the new look in emergency lighting design. Its sleek low profile body and transparent lamp shield combine to make a contemporary style that's just right for today's aesthetic demands. Whether it is featured in its standard off-white color or optional black, the PROVIDER will complement a variety of interiors in stores, offices, theaters, restaurants and shopping malls. PROVIDER is versatile too, its body, measuring only 11" x 5", can be mounted in any orientation on walls or ceilings.

Standard Features

- Completely self-contained
- UL listed to Standard 924
- 120/277 Vac input standard
- Fully adjustable self-locking heads
- 6 volt High Intensity Tungsten (HIT) lamps and mirrored reflectors supply generous amounts of emergency lighting.
- Maintenance-free recombination battery provides 90 minutes of emergency operation.
- Reliable integrated circuitry:
- Constant potential, temperature compensated, current limited charger recharges the battery to rated capacity per UL Standard 924
- Low Voltage Battery Disconnect prevents deep discharge damage
- Brownout Protection-when utility power drops so low that area lighting lamps dim or extinguish, the PROVIDER will automatically activate

- Battery Lockout-saves labor and prevents battery discharge during installation
- Instantaneous transfer
- Long life LED charge monitor light
- Rocker type test switch
- Sealed, dust-tight transfer relay



Advanced Diagnostics (optional)

Enjoy the peace of mind provided by Emergi-Lite's advanced diagnostic circuitry. The AD circuit monitors the every critical function of the unit and provides an audible and visual indicator when a fault is detected. Non-audible versions available as well. The Provider Series 's AC quick-connect plug, battery lockout feature and snap-together design make installation fast and easy. With the AC quick-connect plug, contractors simply make the AC connection to the plug, mount the back plate and plug in the unit. The battery lockout feature is an AC activated load switch that prevents the batteries from discharging until the unit is energized with AC power. This allows the contractor to install the unit and connect the batteries in one convenient operation. A universal mounting pattern, keyhole slots and a conduit knock-out provide alternate mounting methods.

Unit Warranty*

Entire unit (excluding lamps) carries a 3-year Full Warranty.

Battery Warranty*

Sealed Lead Calcium: 8-year life expectancy. 3-year Full Warranty, plus 3-year pro rata warranty.

*Subject to proper installation and maintenance.

How to Order MODEL EXAMPLE

Series	Lamp Types / Wattage
6PRO = Remote fixture	-10 = 6V - 10.8 total unit wattage
12PRO = Remote fixture	-2(ZF) = 12V - 18 total unit wattage
24PRO = Remote fixture	-2(ZN) = 24V - 18 total unit wattage

Outline and Dimensions

