

Models EF21R / EF24



Decorative square thermoplastic light prismatic diffusing lens - metal reflector

Emergency Lighting Fixtures for Remote Mounting



Fully recessed metal decorator square - prismatic diffusing lens - metal reflector

semi-recessed, fully recessed or surface type



General Information

Remote SQUARE-LITE to match SQ Series shown in the Decorative Unit Equipment. Constructed from high impact, resistant thermoplastic with metal reflector and prismatic acrylic lens.

Finish: Back box: Black satin (EF24)
Front case: Matte off white

Mounting: Available for surface, or fully recessed mounting. Fully recesses into T-bar or exposed Z-spline ceilings. Supporting bars or rods supplied by others.

Dimensions: EF24: Trim plate: 9"x 9" x 4" deep
Back box: 8 1/2" x 8 1/2" x 1 3/4" deep
EF21R: Trim plate: 10 5/8"x 10 5/8"
Back box: 8 3/4" x 8 3/4" x 3 1/4" deep

Lamp: All lamps must be specified in the part number when ordering. EF24 series may use:

- Wedge base incandescent
- Double contact Bayonet base
- Bi-pin halogen

Standard Features

Lamp type(s), voltage and maximum wattage available for fixture are shown under lamp description. Determine lamp type, voltage and wattage required for your application, then select lamp from Lamp Chart in the Charts & Diagrams section. Do not exceed fixture wattage rating. (20 watt MAX)

Include lamp suffix and voltage as suffix to model number. **VOLTAGE MUST BE STATED.**

How to Order MODEL EXAMPLE

Series	Lamp Types / Wattage*	Colour
EF21R	(HA) = 6V - 6 watts (HF) = 12V - 8 watts (II) = 24V - 9 watts ("I" HIT Series Chart)	Front trim = Off-white
EF24	(IA) = 6V - 6 watts (IE) = 12V - 8 watts (II) = 24V - 9 watts ("I" HIT Series Chart)	

Note: Specify two (2) lamps

Outline and Dimensions

