City of Chicago Approved Chicago Prestige™ Series

Edge-lit recessed, ceiling-mount only, LED exit sign



In high visibility areas, the Chicago Prestige[™] exit sign provides elegant designer details including a clear acrylic panel, recessed ceiling mount design, and brushed aluminum trim plate.

Construction

- Clear acrylic panel provides optimum light transmission. Illumination is 100% in both AC and emergency mode
- Housing: Fully-recessed, 20-gauge galvanized steel back-box; equipped with hanger bars for installation between joists or a suspended ceiling
- Rugged cast brushed aluminum trim plate (optional colors available)
- · White LED light source, 10-year life expectancy

Mounting

- Hanger bars included for lay-in installation in T-bar grid
- Housing provided with conduit knock-out 1/2" top, back and end
- · Flat trim plate used for recessed ceiling mount
- · only applications

Special wording panels

Available. Contact your sales representative with your design requirements

Electronics

- Optional Advanced Diagnostics
- 120-277 60HZ

Approvals

- UL 924 listed
- · City of Chicago Approved

Warranty

Unit has a five-year limited warranty
 Detailed warranty terms located online at:
 www.emergi-lite.com/usa/files/EL_Warranty.pdf








Dimensions

Dimensions are approximate and subject to change



Arrow (chevron) designation









Wording and chevrons not to scale. For illustration purposes only.

Power consumption

Model	AC specs			DC specs	
AC-only	120 to 277VAC	Less than 1.4W			
AC/DC-remote	120 to 277VAC	Less than 1.4W	6 to 24VDC	Less than 1.4W	
Self-powered	120 to 277VAC	Less than 2.3W	Ni-Cd battery	Min. 90 minutes	
Self-powered diagnostic	120 to 277VAC	Less than 2.3W	Ni-Cd battery	Min. 90 minutes	

Backbox (order as a separate item)

 Description
 Suffix

 Backbox kit flat trim Chicago
 BBKTRCC-E

Accessories (order as a separate item)

Description	Suffix ¹		
Special wording	Contact your sales representative		
Two 27-inch adjustable bar hangers ¹	ТВН		

¹Bar hangers supplied with unit, order as replacement only

How to order

Housing color Custom specifica	ation Model	Legend and panel	Trim plate	Options
Blank= Brushed aluminum W= White B= Black BR= Dark bronze (painted) PB= Polished brass CH= Polished Chrome Example: BCCPLX#2AF	go PLX= AC only PLXDC= AC/DC-remote 6-24V PLX2CKT= AC-dual circuit PLXN= Self-powered PLXND= Self-powered diagnostic	#2A= Single face, STAIRS, no arrow #17A= Double face, STAIRS, no arrow #5A= Single face, STAIRS, arrow right #8A= Single face, STAIRS, arrow left #11A= Single face, STAIRS, double arrow #23A= Double face, STAIRS, double arrow #20A= Double face, (1) STAIRS, (2) STAIRS single arrow #3= Single face, EXIT, no arrow #18= Double face, EXIT, no arrow #6= Single face, EXIT, arrow right #9= Single face, EXIT, double arrow #12= Single face, EXIT, double arrow #24= Double face, EXIT, double arrow #21= Double face, (1) EXIT, (2) EXIT, single arrow LP= Panel shipped separately		-DL= Damp locations -X= Less backbox¹

¹Order backbox as a separate item