

ELX400 SQ Series

The **ELXN400 SQ Programmable Series** confronts job site mounting situations "head-on". The fully adjustable SQ heads can be configured for top mounted, side mounted, or anywhere in between without disassembly or re-wiring.

UL Listed

Complies with NEC, Life Safety Code and OSHA.
Damp location listing is standard on all models.



We have added two new units to the ELX400 SQ Series

- ▣ **Combination Red LED Exit with Self Diagnostics**
- ▣ **Red LED Exit with No Heads, Remote Capacity (22 watts) and Self Diagnostics**

Standard Features

Reliability

- The **Escort II ELXN400 SQ Series** has a three-year full warranty (excluding lamps, pilot lights and fuses)

Housing

- Injection-molded UV stabilized thermoplastic housing, faceplates, and canopy
- UL 94, 5Va flame rating
- Innovative, snap-together design allows for fast installation
- Replaceable directional chevron inserts are easily removed and reinserted
- Two faces, backplate, and canopy
- Two fully adjustable glare-free SQ light heads for egress light

Mounting

- Wall or ceiling mounting
- Canopy snaps to housing with a twist-lock feature tightly securing the canopy to the housing

ELX400 SQ Models with Auto-Diagnostics

Auto-Diagnostic / Self-Test circuitry is available optionally on red LED self-powered models only. This circuitry is programmed to ensure the equipment readiness and reliability by continuously monitoring every critical function of the unit. If a problem occurs, the bi-color pilot light of the unit will change color from solid green to a flashing red light, indicating a fault. A detailed diagnostic legend is available near the pilot light provides fault identification for the maintenance personnel: battery disconnect, battery failure, charger failure, transformer failure, lamp failure, remote lamp failure, LED strip failure (Exit signs only). The self-test feature will simulate a power loss for one minute every 30 days, 30 minutes on the 6th month, and 90 minutes on the 12th month of the year after installation.

Accessories (order as a separate item)

- Wire Guard (heads in any position)WG10-E
- Replacement battery860.0004-E
- Replacement lamp570.0012-E

* Do not exceed rated unit capacity.

How To Order

ELXN400 Series Self-powered	R Stencil Face (letters) R = Red G = Green	2SQ Light Heads -0= Combo no heads* -2SQ= Lamp standard 6V 5.4W	R Capacity Indicator Blank =No remote capacity R = remote capacity*	-AD Options Blank= No options -AD= Advance Diagnostics*
-----------------------------------	---	--	--	--

Examples:

RED Stencil Face Models	GREEN Stencil Face Models
ELXN400R-2SQ	ELXN400G-2SQR
ELXN400R-OR-AD	ELXN400G-2SQ
ELXN400R-2SQR	
ELXN400R-2SQR-AD	

*only available with Remote Capacity AD and red stencil

* Do not exceed rated unit capacity.



Electrical Features

Electrical

- 120/277VAC dual voltage operation
- Low power consumption - LED's
- LED indicator light and push button test switch
- Remote capacity exit with two heads may power additional remote heads up to 6 Volt, 12 watts
- Remote capacity exit with no heads may power additional remote heads up to 6 Volt, 22 Watts.
- Low voltage battery disconnect

Lamps

- LED, Light Emitting Diodes
- LED lamps are operated in normal (AC input) and emergency (DC input) modes.
- 2 x 6V 5.4 watts DC T5 wedge base lamps for emergency mode

Battery

- Sealed maintenance-free lead-calcium battery
- Additional battery available for 12 watts remote load or extended unit run time (see How To Order).

Outline and Dimensions

Dimensions are approximate and subject to change.

