

Remote Fixtures Surface Mounted Series

Furnished complete with lamps as specified in the parenthesis. For alternate lamp selection, see lamp data sheet.

Lamp Series Selection Chart

I = High intensity tungsten (HIT) double contact bayonet base	X = Sealed beam halogen*
U = Sealed beam tungsten	Z = High intensity incandescent wedge base
H = BI-PIN halogen*	M = MR16 lamps*

*Available at additional cost

EF14

Description:
Rectangular fixture with diffused lens polycarb

Color:
White baked enamel (specify other)

Mounting:
Surface (wall or ceiling)

Dimensions:
8-1/4" X 4-1/2" X 3" deep

Lamps:
Series: I (See Lamps Data Chart)

To Order:
6 volt-EF14(IA)-9 watts
12 volt-EF14(IE)-9 watts
24 volt-EF14(II)-9 watts



EF9 / EF9D

Description:
Single and double compact adjustable decorative lighting head - UL Listed thermoplastic

Color:
Off-white (WT) (black optional) (BK)

Mounting:
Surface (wall or ceiling) direct to 4" octagonal or single-gang box

Lamps:
Series: Z or H (See Lamp Data Chart)

To Order:
EF9: 6 volt-EF9(ZD)-9 watts
12 volt-EF9(ZF)-9 watts
24 volt-EF9(ZN)-9 watts
EF9D: 6 volt-EF9D(ZD)-9 watts*
12 volt-EF9D(ZF)-9 watts*
24 volt-EF9D(ZN)-9 watts*

*Wattages doubles for "D" 2-lamp version



EF16

Description:
Ceiling or wall mounted par 36 - adjustable in two planes to 45°

Color:
Off-white baked enamel (specify other)

Mounting:
Surface; three (3) 1/2" conduit knockouts provided

Dimensions:
8-1/2" X 3-1/2" deep

Lamps:
Series: H, I, U, X or Z (See Lamp Data Chart)

To Order:
6 volt-EF16(IA)-9 watts
12 volt-EF16(IE)-9 watts
24 volt-EF16(II)-9 watts ("I" HIT lamp only)



EF10 / EF10D

Description:
Single and double MR16 indoor lighting head with fully adjustable swivel - all thermoplastic construction

Color:
Off-white (WT)(black optional) (BK)

Mounting:
Direct to 4" octagonal electrical box

Lamps:
MR16 (Series M)

To Order:
EF10: 6 volt-EF10(MI)-6 watts
6 volt-EF10(MJ)-10 watts
12 volt-EF10(MK)-12 watts
12 volt-EF10(MG)-20 watts
EF10D: 6 volt-EF10(MI)-6 watts*
6 volt-EF10(MJ)-10 watts*
12 volt-EF10(MK)-12 watts*
12 volt-EF10(MG)-20 watts*

*Wattages doubles for "D" 2-lamp version



EF18 / EF18D

Description:
Single and double adjustable decorative lighting head - all thermoplastic construction

Color:
Off-white color (WT) (black optional) (BK)

Mounting:
Direct to 4" octagonal or single-gang box

Lamps:
Series: H, I, U, X or Z (See Lamp Data Chart)

To Order:
EF18: 6 volt-EF18(ZD)-9 watts
12 volt-EF18(ZF)-9 watts
24 volt-EF18(ZN)-9 watts
EF18D: 6 volt-EF18D(ZD)-9 watts*
12 volt-EF18D(ZF)-9 watts*
24 volt-EF18D(ZN)-9 watts*

*Wattages doubles for "D" 2-lamp version



Surface Mounted Series *Remote Fixtures*

EF23 / EF23D



Description:

Single adjustable decorative lighting head - all thermoplastic construction

Color:

Off-white (WT), black (BK)

Mounting:

Direct to 4" octagonal or single-gang box round mounting canopy standard

Lamps:

Series: H or Z

(H = 6, 8 and 12 watt lamps only)

(Z = 5.4, 9 and 12 watt lamps only)

To Order:

EF23: 6 volt-EF23(ZP)-5.4 watts

6 volt-EF23(ZD)-9 watts

12 volt-EF23(ZF)-9 watts

12 volt-EF23(ZG)-12 watts

EF23D: 6 volt-EF23D(ZP)-5.4 watts*

6 volt-EF23D(ZD)-9 watts*

12 volt-EF23D(ZF)-9 watts*

12 volt-EF23D(ZG)-12 watts*

*Wattage doubles for "D" 2-lamp version



EF28 / EF28D



Description:

Single or double metal housing head with fully adjustable swivel

Color:

Head: chrome finish (off-white optional)

Mounting:

EF28: Surface; 1 MPC - 1 plate supplied

EF28D: Surface; 3 MPC - 2 plate supplied

Dimensions:

EF28: Mounting plate 2-1/2" X 4-1/4"

EF28D: Mounting plate 6-7/16" X 4-1/2"

Lamps:

Series: H, I, U, X or Z

(See Lamp Series Chart)

To Order:

EF28: 6 volt-EF28(IA)-6 watts

12 volt-EF28(IE)-9 watts

24 volt-EF28(II)-9 watts

EF28D: 6 volt-EF28D(IA)-6 watts*

12 volt-EF28D(IE)-9 watts*

24 volt-EF28D(II)-9 watts*

*Wattage doubles for "D" 2-lamp version



EF24



Description:

Decorative square thermoplastic light prismatic diffusing lens - metal reflector

Color:

Front trim: off-white

Back box:

black

Mounting:

Surface (wall or ceiling).

For semi-recessed mounting, order EF24R, semi-recessed deep mounting box included (8-1/2" X 8-1/2" X 1-3/4" deep)

Dimensions:

9" X 9" X 4" deep

Lamps:

Series: H, I, or Z (See Lamp Series Chart)

To Order:

EF24: 6 volt-EF24(IA)-6 watts*

12 volt-EF24(IE)-8 watts*

24 volt-EF24(II)-9 watts* ("I" HIT lamp only)

Note: Specify two (2) lamps

*Wattage doubles for 2-lamp version



EF32 / EF32D



Description:

Single miniature 3" diameter X 4-1/4" fully adjustable aluminum cylinder complete with matching round mounting plate

Color:

Off-white baked enamel finish standard, black (BK)

Mounting:

Direct to 4" octagonal box

Lamps:

"H" BI-PIN halogen lamp (6 or 12 VDC only)

To Order:

EF32: 6 volt-EF32(HA)-6 watts

12 volt-EF32(HF)-8 watts

EF32D: 6 volt-EF32D(HA)-6 watts*

12 volt-EF32D(HF)-8 watts*

*Wattage doubles for "D" 2-lamp version

