



# 6 Volt Recessed Down Light **GS Series**

The **GS Series** combines the function of a well designed emergency lighting fixture with the style of a desirable looking recessed downlight. Several models and lamp choices provide flexibility in the emergency lighting layout while keeping an aesthetically pleasing look to the interior.

## UL Listed

Complies with NEC, Life Safety Code and OSHA. Approved use in the Commonwealth of Pennsylvania and New York City.

## Sealed Maintenance-Free Batteries

- Nickel-Cadmium
- Lead-Calcium
- Long Life Lead

## Standard Features

### Reliability

The GS Series comes complete with a 3-year full warranty, excluding lamps, pilot lights and fuses.

### Unit Data

**Low Profile Trim Ring\***, molded in tough polycarbonate, has a semi-gloss white finish to complement a variety of ceilings. The fully recessed back box is constructed of 20-gauge steel.

**Adjustable Gimbal** directs the light from one PAR 36 light head.

**Inconspicuously Mounted but Easily Accessed...** the test switch and LED pilot light are located on the side of the lamp ring standard\*\*.

**Easy To Install...** A slide out chassis and two quick-connect plugs make installation and servicing easy. Adjustable hanger bars are supplied with each unit.

### PulsePlus Charger

PulsePlus circuitry offers 120/277 Vac 60 Hz., 0.3/0.15 Amp, fused output circuit(s), long life LED pilot indicator, temperature compensated, sealed relay, low voltage battery disconnect, brownout protection and lockout (automatic battery connect).

## Optional Features

### Description

Black ..... **Add Prefix** .....B

**Add Suffix**

New York City (12 watt lamp) .....-NYC\*

\* NYC version includes a metal trim and pivot assy.

NYC version has the test switch and pilot lamp located on the gimbal ring.

### Accessories (order as a separate item)

Remote Test Switch (metal face plate).....RTS

Remote Text Switch (plastic face plate) .....RTS-1

## How To Order (example)

For standard units without options only order Series, Battery, and Watts

Options are added to units by listing suffix at end of model #

GS	C	18	UA	- NYC
Series	Battery Type	Watts	Lamp Option*	NYC
	Nickel-Cadmium	for 90 min.	6V 9W Sealed Beam Incandescent	Approved Model
			* see lamp data for other lamp wattages.	

NOTE: Includes standard lamp (570.0016)



## Unit Rating Chart

Each unit is furnished with one 6 volt 9 watt wedge-base lamp. Other wattages available, see lamp data sheet for selection of PAR lamps.

UNIT EQUIPMENT - NO REMOTE CAPABILITY						
Sealed Maintenance-Free Battery Types	D.C. Voltage	Model Number	*Watts to 871/2% of rated battery voltage			
			11/2 hrs.	2 hrs.	3 hrs.	4 hrs.
Lead-Calcium	6	GSM10-BH	8	6	-	
Long Life Lead	6	GSE9-BH	8	7	-	
UNIT EQUIPMENT - WITH REMOTE CAPABILITY						
Nickel-Cadmium	6	GSC18-BH	18	12	9	
Long Life Lead	6	GSE18-BH	18	11	8	

\*National Electrical Code Specification

New York City Approved

## Outline and Dimensions

Dimensions are approximate and subject to change.

